# myKAMAR

## REFERENCE:
# BLK0033

## LED WARNING LIGHTBAR 305X158 R10 R65 MAGNET

### WARNINGS FOR THE USER:

- Do not look directly into the light - it may cause damage or even loss of vision.
- Install only in specialized workshops or professional services.
- Use in open space only.
- Use in accordance to the purpose.

### INSTALLATION INSTRUCTIONS:

- It should be used exclusively in accordance with intended use.
- **Mount exclusively in specialized workshops.**
- **The connection between the lamp and vehicle's installation should be isolated with heat-shrink tube, or, alternatively, with isolating tape, to avoid getting water and moisture to the copper wire of the lamp, which can damage electronic components. When it comes to lamp and plug, the plug should be mounted safely.**
- **Do not cut off tinned ends.**
- **Lamps must be installed only in accordance with UNECE regulations**
- Only mount the lamp to a flat, metal, dry, cleaned and degreased roof surface. The maximum speed of movement of the vehicle with a warning lamp attached with a magnet to the roof surface is 50km/h. Take special care in windy conditions. Do not unscrew the lamp, it will lose its water resistance.

**TRUCK LED**  **TL**

# www.myKAMAR.com

## PHOTO AND TECHNICAL DRAWING:



R10 — UNECE Regulation 10 Approved
R65 — UNECE Regulation 65 Approved
IP 67

## TECHNICAL SPECIFICATIONS:

| MATERIAL | LED/LM QUANTITY | MOUNTING | WIRE | FUNCTION | WATT | VOLTAGE | CERTIFICATES | PACKING/ WEIGHT |
|---|---|---|---|---|---|---|---|---|
| • Lens: PC<br>• Housing: ABS | • 84 | • magnet | • 3,5m straight cable with plug for lighter socket | • 2 warnings flashes | • 38W | • 12 V/24V | • ECE R10<br>• ECE R65 | • cart. dim.: 337x244x90mm<br>• weight: 1500g<br>• 10 pcs/bulk box |