

WARNINGS FOR THE USER:

- Do not look directly into the light it may cause damage or even loss of vision.
- Install only in specialized workshops or professional services.
- · Use in open space only.
- Use in accordance to the purpose.

INSTALLATION INSTRUCTIONS:

- It should be used exclusively in accordance with intended use.
- · Mount exclusively in specialized workshops.
- The connection between the lamp and vehicle's installation should be isolated with heat-shrink tube or alternatively with isolating tape to avoid getting water and moisture to the copper wire of the lamp which can damage electronic components. When it comes to lamp and plug, the plug should be mounted safely.
- · Do not cut off tinned ends.
- Lamps must be installed only in accordance with UNECE regulations.





PHOTO:





TECHNICAL SPECIFICATIONS:













MATERIAL	LIGHT SOURCE	OEM	FUNCTION	WATT	VOLTAGE	CERTIFICATES	PACKING - BULK BOX
» Lens: PC » Housing: PA6	» bulbs H1 » bulbs H3 » bulbs H7 »bulbs W5W » bulbs P21W	» 5010578478	 » low-beam light » high-beam light » position front » indicator » rear fog lamp 	» 70W » 70W » 5W » 21W » 70W	» 12/24V	» ECE R6 » ECE R7 » ECE R19 » ECE R112	» cart. dim.: 620x270x260mm » weight: 3380g » 2 pcs/bulk box

We reserve the right to change technical data and any errors. Photos and specifications are for reference only, and the actual product may vary slightly. Reproduction in whole or parts of the catalog without written authorization is prohibited.